

DSC3/DSF3/DSS3

Door Stations

Elegant Looks

An Array of Solutions

Communications
for Everyday Living

Oil-rubbed Bronze. Satin Nickel. Polished Brass or Chrome and Ivory. ELAN has a Door Station that will enhance every entranceway of your home.

With a built-in camera, or without. Surface-mounted, or flush against the brick. ELAN has a Door Station solution to meet your tastes and needs.

Talk with visitors at the door — any door — from any phone in the home. Let them in, if you're so inclined, with our door-latch feature. And, see who's at any entryway on ELAN touch panels or TVs from anywhere in the home.

Living With ELAN

It's Your Home . . .

. . . and it deserves the best, inside and out. ELAN Door Stations, along with the COM2 Communication Controller, allow you to use your own telephones to communicate with visitors at the door. Your visitors will see the ultimate in style and elegance gracing your entranceways, and appreciate the simplicity and clarity of the communications.

Simple, Convenient and Secure

ELAN Door Stations provide you with full 2-way communications and door latch control from your touch-tone telephones. A simple #-D (for Door) from any touch-tone phone allows you to speak with visitors at the door. Another simple button press ("0") activates the door latch to let them in, if so inclined. The DSC3, with its on-board color camera, gives you the option of seeing who's there before you even pick up the phone.

Designed for Quality and Longevity

ELAN door station and doorbell faceplates are constructed from 0.4" thick brass and coated

with a tarnish-proof zirconium nitride finish that can withstand the harshest of environments and continue to look beautiful year after year. The crystal-clear sounding speaker and microphone are sealed tight against the weather, and the CCTV camera (DSC3 only) is a hi-res, low-lux, wide-angle color camera designed specifically for outdoor environments and extremes in temperature.

COM2 Communications Controller

ELAN Door Stations are designed to work with the COM2, ELAN's next-generation, in-home communications controller, which transforms any multi-room audio system into a multi-line communications network that seamlessly integrates intercom, telephone and automation features to create an environment of easy whole-house communications.

In addition to whole-house paging, phone-to-phone intercom, and much more, the COM2 allows for the connection of four ELAN Door Stations (each of which can be accessed independently) and 10 user-selectable door chimes. With the COM2's automation features and a DSC3, live camera images can even be programmed to pop up automatically on any TV or ELAN touch panel whenever someone rings the doorbell.

(DSC3 shown in Oil-rubbed Bronze)



Communications for Everyday Living

www.elanhomesystems.com

ELAN[®]
HOME SYSTEMS

Features & Specifications

3 Door Station Models

- Full 2-way communications with visitors at up to four doors/entryways from any phone in the house
- Ideal for gates! Can be located up to 1000 ft. away from head-end
- Available in flush- & surface-mount models
- Installs horizontally and vertically
- Color-camera version for viewing visitors on TVs & ELAN touch panels
- Lighted doorbell button
- Door-latch activation
- Built to withstand the harshest environments
- Uses only a single run of Cat-5 cable for audio & camera
- COM2 Communications Controller required
- Available in 5 finishes: Oil-rubbed Bronze, Satin Nickel, Polished Brass, Polished Chrome & Ivory (Shown below)



DSC3 Flush-Mount Door Station w/ Lighted Doorbell Button & Color CCTV Camera

DSF3 Flush-Mount Door Station w/ Lighted Doorbell Button

DSS3 Surface-Mount Door Station w/ Lighted Doorbell Button

Speaker:8 Ohms, sealed back polyester cone
 Microphone:High-gain omni-directional condenser
 Door Latch Relay:12VDC coil, 2A contact rating
 Wiring Requirements:Cat-5, 1000 ft. max

Color Camera Specifications (DSC3 Only)

Imager:1/3 in. CCD
 Auto Iris:1/50 – 1/100,000 sec.
 Lux:0.5 min.
 Resolution:480 TV lines
 Horizontal Viewing Angle:120°
 Vertical Viewing Angle:100°
 Swivel:+15°/-15° left to right
 Video Output:1V peak-to-peak
 Video Output Impedance:75 Ohms
 Power Requirements:12VDC @ 130mA
 (camera power supply included)

ELAN Home Systems reserves the right to change hardware and specifications without notice.

(DSF3 shown in Polished Brass)



(DSS3 shown in Satin Nickel)



Two-Year Limited Warranty
www.elanhomesystems.com